

**SYLGARD(R) 184 SILICONE ELASTOMER KIT  
(BASE information is below)**

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
Date of first issue: 11/20/2014

**SECTION 1. IDENTIFICATION**

Product name : SYLGARD(R) 184 SILICONE ELASTOMER KIT (BASE information is below)

Product code : 000000000001064291

**Manufacturer or supplier's details**

Company name of supplier : Dow Corning Corporation

Address : South Saginaw Road  
Midland Michigan 48686

Telephone : (989) 496-6000

Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

**Recommended use of the chemical and restrictions on use**

Recommended use : Corrosion inhibitors  
Electrical industry and electronics

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Silicone

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
Ethylbenzene	100-41-4	>= 0.1 - < 1

**SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

## SYLGARD(R) 184 SILICONE ELASTOMER KIT (BASE information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 03/19/2016
3.0	10/20/2016	802554-00009	Date of first issue: 11/20/2014

- If inhaled : If inhaled, remove to fresh air.  
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides  
Silicon oxides  
Formaldehyde
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

## SYLGARD(R) 184 SILICONE ELASTOMER KIT (BASE information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 03/19/2016
3.0	10/20/2016	802554-00009	Date of first issue: 11/20/2014

for fire-fighters

Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid inhalation of vapor or mist. Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Handle in accordance with good industrial hygiene and safety practice. Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers. Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

# SYLGARD(R) 184 SILICONE ELASTOMER KIT

(BASE information is below)

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
 Date of first issue: 11/20/2014

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
		TWA	100 ppm 435 mg/m <sup>3</sup>	NIOSH REL
		ST	125 ppm 545 mg/m <sup>3</sup>	NIOSH REL

### Biological occupational exposure limits

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	0.15 g/g creatinine	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
 Ensure adequate ventilation, especially in confined areas.  
 Minimize workplace exposure concentrations.

### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection  
 Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often!  
 For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical

## SYLGARD(R) 184 SILICONE ELASTOMER KIT (BASE information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 03/19/2016
3.0	10/20/2016	802554-00009	Date of first issue: 11/20/2014

---

resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.  
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: colorless
Odor	: slight
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: > 100 °C
Flash point	: 121.1 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Self-ignition	: The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapor pressure	: No data available

# SAFETY DATA SHEET

**DOW CORNING**

## SYLGARD(R) 184 SILICONE ELASTOMER KIT (BASE information is below)

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
Date of first issue: 11/20/2014

---

Relative vapor density : No data available

Relative density : 1.11

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : 5000 cSt

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Use at elevated temperatures may form highly hazardous compounds.  
Can react with strong oxidizing agents.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

**Hazardous decomposition products**  
Thermal decomposition : Formaldehyde

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

---

**SYLGARD(R) 184 SILICONE ELASTOMER KIT  
(BASE information is below)**

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
Date of first issue: 11/20/2014

---

**Acute toxicity**

Not classified based on available information.

**Ingredients:****Ethylbenzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg  
Acute inhalation toxicity : LC50 (Rat): 17.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Ingredients:****Ethylbenzene:**

Species: Rabbit  
Result: No eye irritation

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Ingredients:****Ethylbenzene:**

Test Type: Human repeat insult patch test (HRIPT)  
Routes of exposure: Skin contact  
Result: negative

**Germ cell mutagenicity**

Not classified based on available information.

**Ingredients:****Ethylbenzene:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
: Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

# SYLGARD(R) 184 SILICONE ELASTOMER KIT

(BASE information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 03/19/2016
3.0	10/20/2016	802554-00009	Date of first issue: 11/20/2014

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo  
 Species: Mouse  
 Application Route: Inhalation  
 Method: OECD Test Guideline 486  
 Result: negative

### Carcinogenicity

Not classified based on available information.

### Ingredients:

#### Ethylbenzene:

Species: Rat  
 Application Route: Inhalation  
 Exposure time: 104 weeks  
 Result: positive  
 Remarks: The mechanism or mode of action may not be relevant in humans.

#### IARC

Group 2B: Possibly carcinogenic to humans

Ethylbenzene 100-41-4

#### OSHA

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

### Ingredients:

#### Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
 Species: Rat  
 Application Route: inhalation (vapor)  
 Method: OECD Test Guideline 415  
 Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
 Species: Rat  
 Application Route: Inhalation  
 Method: OECD Test Guideline 414  
 Result: negative

### STOT-single exposure

Not classified based on available information.



## SYLGARD(R) 184 SILICONE ELASTOMER KIT (BASE information is below)

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
Date of first issue: 11/20/2014

### STOT-repeated exposure

Not classified based on available information.

#### Ingredients:

##### Ethylbenzene:

Routes of exposure: inhalation (vapor)  
Target Organs: Auditory system  
Assessment: Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

### Repeated dose toxicity

#### Ingredients:

##### Ethylbenzene:

Species: Rat, female  
LOAEL: 75 ppm  
Application Route: inhalation (vapor)  
Exposure time: 104 Weeks

### Aspiration toxicity

Not classified based on available information.

#### Ingredients:

##### Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Ingredients:

##### Ethylbenzene:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (green algae)): 5.4 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l Exposure time: 7 d

**SYLGARD(R) 184 SILICONE ELASTOMER KIT  
(BASE information is below)**

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
Date of first issue: 11/20/2014

---

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 209

**Persistence and degradability****Ingredients:****Ethylbenzene:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 70 - 80 %  
Exposure time: 28 d

**Bioaccumulative potential****Ingredients:****Ethylbenzene:**

Bioaccumulation : Species: Fish  
Bioconcentration factor (BCF): < 100  
Remarks: Based on data from similar materials

Partition coefficient: n-octanol/water : log Pow: 3.6

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

---

# SYLGARD(R) 184 SILICONE ELASTOMER KIT

(BASE information is below)

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
 Date of first issue: 11/20/2014

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number : UN 3082  
 Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
 (Xylene)  
 Class : 9  
 Packing group : III  
 Labels : CLASS 9  
 ERG Code : 171  
 Marine pollutant : no  
 Remarks : THE ABOVE INFORMATION ONLY APPLIES TO PACKAGE  
 SIZES WHERE THE HAZARDOUS SUBSTANCE MEETS  
 THE REPORTABLE QUANTITY.

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know****CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Xylene	1330-20-7	100	20408
Ethylbenzene	100-41-4	1000	*
Toluene	108-88-3	1000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 302 Extremely Hazardous Substances Threshold Planning Quantity**

|| This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Ethylbenzene	100-41-4	0.1 - 1 %
--------------	----------	-----------

**US State Regulations****Pennsylvania Right To Know**

Dimethyl Siloxane, Dimethylvinylsiloxo-terminated	68083-19-2
---	------------

# SYLGARD(R) 184 SILICONE ELASTOMER KIT

(BASE information is below)

Version	Revision Date:	SDS Number:	Date of last issue: 03/19/2016
3.0	10/20/2016	802554-00009	Date of first issue: 11/20/2014

Dimethylvinylated and trimethylated silica	68988-89-6
Xylene	1330-20-7
Ethylbenzene	100-41-4
Toluene	108-88-3

**California Prop. 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

Ethylbenzene	100-41-4
--------------	----------

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

Toluene	108-88-3
---------	----------

**The ingredients of this product are reported in the following inventories:**

NZIoC : All ingredients listed or exempt.

REACH : For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

PICCS : All ingredients listed or exempt.

KECI : All ingredients listed, exempt or notified.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from inventory listing.

IECSC : All ingredients listed or exempt.

AICS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

TCSI : All ingredients listed or exempt.

# SYLGARD(R) 184 SILICONE ELASTOMER KIT


(BASE information is below)

Version 3.0      Revision Date: 10/20/2016      SDS Number: 802554-00009      Date of last issue: 03/19/2016  
 Date of first issue: 11/20/2014

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration;

**SYLGARD(R) 184 SILICONE ELASTOMER KIT  
(BASE information is below)**

Version	Revision Date:	SDS Number:	Date of last issue: 03/19/2016
3.0	10/20/2016	802554-00009	Date of first issue: 11/20/2014

---

n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/20/2016

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8